

FilterSpec® Pro

FilterSpec® Pro Noir/Incolore FFP3V / AGE130-201-100



DESCRIPTION

Portées ensemble, les lunettes de sécurité et les masques respiratoires nuisent souvent à l'efficacité de l'un et de l'autre. En effet, la monture des lunettes compromet l'étanchéité du masque respiratoire, ce qui entraîne la formation de buée sur les verres et réduit la protection respiratoire. La gamme FilterSpec®Pro combine les deux dispositifs de protection en une seule pièce.

OPTIONS

FilterSpec® Pro Noir/Incolore FFP2V (AGE120-201-100)

FilterSpec® Pro Noir/Incolore FFP3V (AGE130-201-100)

NORMES

EN 170 • EN 149 • EN 166



INFORMATIONS TECHNIQUES



LIGHT TRANSMISSION BREAKDOWN Lens Shade number
2C



Manufacturer's Trademark
JSP Dagger



Medium Energy Impact resists a 6 mm, 0.86g ball @ 120 m/s Maximum protection for goggles.
B



Protection from Liquid Droplets
3



Resistance to Molten Metals and Hot Solids Helmets (optional)
9



Filter Type
P (Protection contre les aérosols solides et liquides)



Activated Carbon Layer
Non

Maximum Total Inward Leakage (TIL)
2%

UK Assigned Protection Factor
20



Exhalation Valve
Oui

Material
Oculaire en polycarbonate

Filter Shelf Life
5 ans



Product Weight
144g



LIGHT TRANSMISSION BREAKDOWN Lens Shade number
1,2



Optical Class (1 – Class 1 – High quality for regular use. 2 – Class 2 – Medium quality for occasional use. 3 – Class 3 – Low quality for exceptional use)
1



The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures. (-5°C and +55°C) Optional
T



Protection from Large Dust Particles (up to 40 um grain size)
4

Classification

FFP3 (Pièce faciale filtrante anti-particules)

Usage

NR (non réutilisable)

Minimum Filtration Efficiency

99% FFP3

Nominal Protection Factor

50

Mask Design

Moulé

Mask Material

Polypropylène

Material

Support de masque en PEHD



BSI Kitemark


Oui

CARACTÉRISTIQUES



Intégré

La conception unique surmonte le problème des masques mal ajustés, des oculaires embués et de la non-conformité qui peut arriver lorsqu'un élément D'EPI en compromet un autre.



Filtration efficace

Les masque de remplacement sont fabriqués à partir de 3 couches pour des performances exceptionnelles. Disponible avec une valve expiratoire à faible résistance pour réduire l'humidité et l'accumulation de CO₂.



Qualité de l'oculaire

Les lunettes masque de protection FilterSpec® Pro sont dotées d'un oculaire à courbure de base de 5,5. Les oculaires de la gamme FilterSpec® ont une courbe de base de 6,5. Les deux offrent une couverture optimale et ont revêtements anti-buée et anti-rayures

GAMME

TÉLÉCHARGEMENTS

[Pack d'images \(ZIP\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 3 / Issued 23 Feb 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.





JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 3 of 3 / Issued 23 Feb 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.

