

## DESCRIPTION

The PSP Allround Nitrile Sandy Pro 10-470 is a high quality glove with a Blue 15 gauge nylon liner and rough nitrile coating in the palm of the hand for an ultimate grip. The back of the glove is open which provides good ventilation and excellent comfort as a result.

The open nitrile coating provides an excellent grip, the coating is (besides the open structure) also liquid-tight and suitable for dry, but also moist and oily environments.

Article PSP 10-470 has been tested and certified in accordance with the European Regulation (EU) 2016/425 and the EN-standards EN420 / EN388:2016.

## CHARACTERISTICS

- ▲ Nylon liner with lycra, 15 gauge
- ▲ Nitrile coating (sandy)
- ▲ Elasticated knitted cuff
- ▲ Good grip in dry, moist and oily environments.
- ▲ Ventilated
- ▲ High wearing comfort
- ▲ Multifunctional
- ▲ Excellent finger dexterity
- ▲ Various sizes available
- ▲ Certification according to: EN420 / EN388:2016

## CERTIFICATIONS

 CAT II	 EN 388:2016 4131X	Abrasion resistance = 4
		Blade cut resistance = 1
		Tear resistance = 3
		Puncture resistance = 1
		Cut ISO 13997 = X

## APPLICATIONS

Construction | Logistics | Industry | Transport | Assembly | Installation | work



## PRODUCT INFORMATION

<b>Material</b>	Liner: Nylon, Coating: Nitrile
<b>Color</b>	Blue / Black
<b>Length (mm)</b>	220-260 Depending on the size
<b>Cuff</b>	Elasticated knitted cuff

## ORDER DETAILS

Size	Item number	Packing Unit
07 / S	2.01.10.470.07	12 x 12 (144 pairs)
08 / M	2.01.10.470.08	12 x 12 (144 pairs)
09 / L	2.01.10.470.09	12 x 12 (144 pairs)
10 / XL	2.01.10.470.10	12 x 12 (144 pairs)
11 / XXL	2.01.10.470.11	12 x 12 (144 pairs)



\*\* Liquid protection: Note! The degree of protection depends on the coating used.  
Cut ISO 13997: The letter A to F indicates the cut resistance according to ISO 13997. X = control not performed or not applicable

