

DESCRIPTION

The PSP Allround Nitrile Foam Plus 10-570 is a glove with a 15 gauge nylon liner covered in a ventilated nitrile foam coating on the palm.

The back of the glove is open, which provides good ventilation and as a result excellent comfort. The open nitrile coating provides a good grip on dry, moist and oily environments.

Article PSP 10-570 has been tested and certified in accordance with the European Regulation (EU) 2016/425 and the EN-standards EN420 / EN388:2016.

CHARACTERISTICS

- ▲ Nylon liner with lycra, 15 gauge
- ▲ Nitrile foam coating
- ▲ Good grip in dry, moist and oily environments.
- ▲ Ventilated
- ▲ High wearing comfort
- ▲ Multifunctional
- ▲ Excellent finger dexterity and abrasion resistance
- ▲ Elasticated knitted cuff (tricot)
- ▲ Various sizes available
- ▲ Certification according to: EN420 / EN388:2016

CERTIFICATIONS

CE CAT II

EN 388:2016



4131X

Abrasion resistance = 4
 Blade cut resistance = 1
 Tear resistance = 3
 Puncture resistance = 1
 Cut ISO 13997 = X



APPLICATIONS

Construction | Logistics | Industry | Logistics | Transport |
 Assembly | Installation | Precision work

-  Allround precision work
-  Allround finger sensitive
-  Allround heavy duty
-  Oil protection

PRODUCT INFORMATION

Material	Liner: Nylon
	Coating: Nitrile Foam
Color	Grey / Black
Length (mm)	220-270 Depends on the size
Cuff	Elasticated knitted cuff

ORDER DETAILS

Size	Item number	Packing Unit
05 / XXS	2.01.10.570.05	12 x 12 (144 pairs)
06 / XS	2.01.10.570.06	12 x 12 (144 pairs)
07 / S	2.01.10.570.07	12 x 12 (144 pairs)
08 / M	2.01.10.570.08	12 x 12 (144 pairs)
09 / L	2.01.10.570.09	12 x 12 (144 pairs)
10 / XL	2.01.10.570.10	12 x 12 (144 pairs)
11 / XXL	2.01.10.570.11	12 x 12 (144 pairs)

Cut ISO 13997: The letter A to F indicates the cut resistance according to ISO 13997. X = Control not performed or not applicable

