

DESCRIPTION

The PSP Allround Nitril Foam Pro DT 10-585 is a glove with a 15 gauge nylon liner covered in a ventilated nitrile foam coating with antislip dots on the palm for extra grip. The back of the glove is open, which provides good ventilation and as a result excellent comfort. The open nitrile coating provides a good grip on dry, moist and oily environments.

Article PSP 10-585 has been tested and certified in accordance with the European Regulation (EU) 2016/425 and the EN-standards EN420 / EN388:2016.

CHARACTERISTICS

- ▲ Nylon liner with lycra, 15 gauge
- ▲ Top quality nitrile foam coating
- ▲ Antislip dots on the palm and fingers for extra grip
- ▲ Good grip in dry, moist and oily environments.
- ▲ Ventilated
- ▲ High wearing comfort
- ▲ Multifunctional
- ▲ Excellent finger dexterity
- ▲ Excellent abrasion resistance
- ▲ Elasticated knitted cuff (tricot)
- ▲ Various sizes available
- ▲ Certification according to: EN420 / EN388:2016

CERTIFICATIONS

 CAT II	 EN 388:2016 4131X	Abrasion resistance = 4
		Blade cut resistance = 1
		Tear resistance = 3
		Puncture resistance = 1
		Cut ISO 13997 = X



PROPERTIES

Construction | Logistics | Industry | Logistics | Assembly | Installation | Precision work



Allround precision work



Allround finger sensitive



Allround heavy duty



Oil protection

PRODUCT INFORMATION

Material	Liner: Nylon
	Coating: Nitril foam + PVC dots
Length (mm)	220-260 Depending on the size
Cuff	Elasticated knitted cuff (tricot)

ORDER DETAILS

Size	Item number	Packing Unit
07 / S	2.01.10.585.07	12 x 12 (144 pairs)
08 / M	2.01.10.585.08	12 x 12 (144 pairs)
09 / L	2.01.10.585.09	12 x 12 (144 pairs)
10 / XL	2.01.10.585.10	12 x 12 (144 pairs)
11 / XXL	2.01.10.585.11	12 x 12 (144 pairs)

Cut ISO 13997: The letter A to F indicates the cut resistance according to ISO 13997. X = Control not performed or not applicable

