


CHUKKA NOIR S3 SRC



Standard EN ISO 20345 : 2011

LEMAITRE

Safety since 1974



memoryfoam
By LEMAITRE

■ 78% high density recycled foam



Sizes 38 to 50

Réf. CHUKS30NR

Product Highlights

- **Upper in water-repellent suede microfiber** : lightness, breathability, tearing and abrasion resistant
- **Breathable perforated microfiber lining**: anti-allergic and anti-microbial, thermoregulatory effect. Prevents odor formation.
- **Memory Foam by Lemaître anti-bacterial insole with memory foam**, energy absorption and dissipation, MSD prevention
- **Derby shoe characterized by open lacing**: easy to put on, adapts to the morphology of the foot. Good hold, comfort. Suitable for strong instep
- **Casual chic style**: elegance and relaxation, a great classic of the city shoe revisited as a safety shoe.



- **Protective toe cap**: HDPC composite fiber.



- **Puncture resistant midsole**: high tenacity composite textile «0» penetration.



Anti-static sole
CARBON PU2D

- **Developed outsole for industrial and urban floors**: good adhesion
- **Large bearing surface**: optimal stability
- **Shock absorption**: preservation of the back and joints
- **Conformal to bent positions**: knee notches and crouching
- **Sculpted studs**: reinforced grip

USE

- Service company, crafts, management.
- Logistics, services, handling, distribution, transportation.



lemaitre-secureite.com

Lemaitre takes care.



CHUKKA NOIR S3 SRC



Standard EN ISO 20345 : 2011

Characteristics of the upper

- **Upper material** : water-repellent microfiber velvet effect
- **Tongue** : water-repellent microfiber
- **Lining** : smooth perforated microfiber

Characteristics of the sole

- **Designation**: CARBON PU2D
- **Material**: polyurethane / polyurethane
- **Antistatic sole**
- **SRA Adhesion coefficient**:
forward flat slip: 0,34 (standard $\geq 0,32$)
forward heel slip: 0,31 (standard $\geq 0,28$)
- **SRB Adhesion coefficient**:
forward flat slip: 0,22 (standard $\geq 0,18$)
forward heel slip: 0,20 (standard $\geq 0,13$)

VARIANT



Chukka noir O2 SRC
CHUKO20NR

Practical information

Weight of one shoe size .42 : g

AET N° 0075/007/161/09/19/2718 EXT 24/12/22

Packaging

Size 38 to 43

shoebox 316 x 204 x 121 mm

carton 635 x 445 x 325 mm

10 shoeboxes per carton

Size 44 to 50

shoebox 355 x 220 x 130 mm

carton 635 x 485 x 355 mm

10 shoeboxes per carton

Gencods

35	3237154507353	43	3237154507438
36	3237154507360	44	3237154507445
37	3237154507377	45	3237154507452
38	3237154507384	46	3237154507469
39	3237154507391	47	3237154507476
40	3237154507407	48	3237154507483
41	3237154507414	49	3237154507490
42	3237154507421	50	3237154507506

Memo for basic and additional requirements of the standard EN ISO 20345 : 2011

Safety footwear

SBP



S1



S1P



S2



S3



200 J toe cap: Protection of the forefoot against shocks and crushing



Anti-perforation insert 1100 N: foot protection against perforation.



Anti-static footwear



Insulation against cold



Shock absorption at the heel



Insulation against heat



Fuel oil-resistant outsole



Outsole resistance to hot contact



Water penetration and water absorption resistant upper



Water resistant



Electrostatic discharge



Ankle protection



Slip-resistance on ceramic floors with detergent



Slip-resistance on steel floors with glycerol



Δ SRC = Δ SRA + Δ SRB

Lemaitre Sécurité

17 rue de Bitschhoffen - CS 90024
F - 67350 Val de Moder
Tél. +33 (0)3 88 72 28 80

lemaitre-securite.com

LEMAITRE

Safety since 1974

DON_LS 04 TDS 0128
update : 19/11/24

Member of
SINAMAP

