

# BALDER S3



Standard EN ISO 20345 : 2011



**LEMAITRE**

*Safety since 1974*



## UTURN® lacing system

- quick lacing
- made of durable nylon
- precision and adjustment

## Ankle protection by Lemaitre

Malleolus protection against side impacts

Sizes 35 to 49

Ref. BALDS30NR

## Product Highlights



- Heavy duty boot available with men's and women's fit.



- 2,0 mm thick high strength leather (against abrasion, tearing and puncture). Tongue with gusset to prevent any infiltration of dust / stones.

- Scuffcap TPU injected: extreme resistance at the front.

- Memory Foam Titan insock for immediate and lasting comfort: antibacterial properties, respects foot hygiene.



- Protective toe-cap: composite HDFC.



- Puncture-resistant midsole: high tenacity fabric "0" penetration.



## TRAILIUM PU2D antistatic sole

- 4 mm studs suitable for construction and heavy duty industry
- Drainage channels for liquids and mud to avoid any risk of aquaplaning
- Lateral edges and 15mm raised heel: reinforced grip on ladder rungs
- Large bearing surface, optimal stability
- Arch support and heel cushioning: MSD prevention

## USAGE

- Civil engineering and Forestry works
- Logistics, automotive
- Shipyard, construction
- Petrochemistry, chemistry



[lemaitre-securite.com](http://lemaitre-securite.com)

An exacting attitude to quality is our culture, safety our priority



# BALDER S3



Standard EN ISO 20345 : 2011

## Characteristics of the upper

- **Upper material:** smooth full grain water-repellent leather with anti-abrasion TPU scuffcap
- **Tongue/gusset:** water repellent leather
- **Collar:** water repellent leather
- **Lining:** 3D microporous fabric

## Characteristics of the sole

- **Designation :** TRAILIUM PU2D
- **Material:** polyurethane / polyurethane
- **Antistatic sole**
- **SRA Adhesion coefficient:**  
forward flat slip: 0,34 (standard  $\geq 0,32$ )  
forward heel slip: 0,31 (standard  $\geq 0,28$ )
- **SRB Adhesion coefficient:**  
forward flat slip: 0,20 (standard  $\geq 0,18$ )  
forward heel slip: 0,17 (standard  $\geq 0,13$ )

## VARIANT



**Borr S3 SRC**  
BORRS30NR

## Practical information

### Women fitting 35-39

Weight of one shoe size 38:  
633 g

**CERTIFICATION N°**  
0075/007/161/07/19/2226  
EXT 13/07/20

### Men fitting 40-49

Weight of one shoe size 42:  
713 g

**CERTIFICATION N°**  
0075/007/161/07/19/2226  
EXT 14/07/20

## Packaging

### size 35 to 39

**shoebox** 345 x 230 x 122 mm

**carton** 635 x 485 x 355 mm

**10 shoeboxes per carton**

### size 40 to 49

**shoebox** 355 x 340 x 130 mm

**carton** 670 x 355 x 360 mm

**5 shoeboxes per carton**

## Gencods

<b>35</b>	3237154405352	<b>43</b>	3237154405437
<b>36</b>	3237154405369	<b>44</b>	3237154405444
<b>37</b>	3237154405376	<b>45</b>	3237154405451
<b>38</b>	3237154405383	<b>46</b>	3237154405468
<b>39</b>	3237154405390	<b>47</b>	3237154405475
<b>40</b>	3237154405406	<b>48</b>	3237154405482
<b>41</b>	3237154405413	<b>49</b>	3237154405499
<b>42</b>	3237154405420		

## Memo for basic and additional requirements of the standard EN ISO 20345: 2011

### Safety Footwear

SBP



S1



S1P



S2



S3



200 J toe-cap: protection of the forefoot against impact and crushing.



Anti-perforation insert 1100 N: foot protection against perforation.



Anti-static footwear



Insulation against cold



Shock absorption at the heel



Insulation against heat



Fuel oil-resistant outsole



Outsole resistance to hot contact



Water penetration and water absorption resistant upper



Water resistant



Electrostatic discharge



Ankle protection



Slip-resistance on ceramic floors with detergent



Slip-resistance on steel floors with glycerol



**SRC = SRA + SRB**

**Lemaitre Sécurité**

17 rue de Bitschhoffen - CS 90024  
F - 67350 Val de Moder  
Tél. +33 (0)3 88 72 28 80

**lemaitre-securite.com**



**LEMAITRE**

*Safety since 1974*

**DON\_LS 04 TDS 0086**  
updated: 21/07/21

Member of  
**SINAMAP**

