

# NJORD S3



Standard EN ISO 20345 : 2011



**LEMAITRE**

*Safety since 1974*



**Ankle protection by Lemaitre**

Malleolus protection against side impacts

**Sizes 35 to 49**

Ref. NJORS30NR

## Product Highlights

- 
**Heavy duty boot available with men's and women's fit.**
- 
**2,0 mm thick high strength leather** (against abrasion, tearing and puncture). Tongue with gusset to prevent any infiltration of dust / stones.
- 
**Scuffcap TPU injected:** extreme resistance at the front.
- 
**Memory Foam Titan insock for immediate and lasting comfort:** antibacterial properties, respects foot hygiene.
- 
**Protective toe-cap:** composite HDFC.
- 
**Puncture-resistant midsole:** high tenacity fabric "0" penetration.



## TRAILIUM PU2D antistatic sole

- 4 mm studs** suitable for construction and heavy duty industry
- Drainage channels for liquids and mud** to avoid any risk of aquaplaning
- Lateral edges and 15mm raised heel:** reinforced grip on ladder rungs
- Large bearing surface,** optimal stability
- Arch support and heel cushioning:** MSD prevention

## USAGE

- Civil engineering and Forestry works
- Logistics, automotive
- Shipyard, construction
- Petrochemistry, chemistry



**lemaitre-securite.com**

An exacting attitude to quality is our culture, safety our priority



# NJORD S3



Standard EN ISO 20345 : 2011

## VARIANT



**BALDER S3 SRC**  
BALDS30NR

## Characteristics of the upper

- **Upper material:** smooth full grain water-repellent leather with anti-abrasion TPU scuffcap
- **Tongue/gusset:** water repellent leather
- **Collar:** water repellent leather
- **Lining:** 3D microporous fabric

## Characteristics of the sole

- **Designation :** TRAILIUM PU2D
- **Material:** polyurethane / polyurethane
- **Antistatic sole**
- **SRA Adhesion coefficient:**  
forward flat slip: 0,34 (standard  $\geq 0,32$ )  
forward heel slip: 0,31 (standard  $\geq 0,28$ )
- **SRB Adhesion coefficient:**  
forward flat slip: 0,20 (standard  $\geq 0,18$ )  
forward heel slip: 0,17 (standard  $\geq 0,13$ )

## Practical information

### Women fitting 35-39

Weight of one shoe size 38:  
662 g

**CERTIFICATION N°**  
0075/007/161/07/19/2226  
EXT 17/09/20

### Men fitting 40-49

Weight of one shoe size 42:  
742 g

**CERTIFICATION N°**  
0075/007/161/07/19/2226  
EXT 18/09/20

## Packaging

### size 35 to 39

**shoebox** 345 x 230 x 122 mm

**carton** 635 x 485 x 355 mm

**10 shoeboxes per carton**

### size 40 to 49

**shoebox** 355 x 340 x 130 mm

**carton** 670 x 355 x 360 mm

**5 shoeboxes per carton**

## Gencods

**35** 3237154403358

**36** 3237154403365

**37** 3237154403372

**38** 3237154403389

**39** 3237154403396

**40** 3237154403402

**41** 3237154403419

**42** 3237154403426

**43** 3237154403433

**44** 3237154403440

**45** 3237154403457

**46** 3237154403464

**47** 3237154403471

**48** 3237154403488

**49** 3237154403495

## Memo for basic and additional requirements of the standard EN ISO 20345: 2011

### Safety Footwear

SBP



S1



(A) (E) (Fo)

S1P



(A) (E) (Fo)

S2



(A) (E) (Fo) (Wru)

S3



(A) (E) (Fo) (Wru)



200 J toe-cap: protection of the forefoot against impact and crushing.



Anti-perforation insert 1100 N: foot protection against perforation.



Anti-static footwear



Insulation against cold



Shock absorption at the heel



Insulation against heat



Fuel oil-resistant outsole



Outsole resistance to hot contact



Water penetration and water absorption resistant upper



Water resistant



Electrostatic discharge



Ankle protection



Slip-resistance on ceramic floors with detergent



Slip-resistance on steel floors with glycerol



**SRC = SRA + SRB**

**Lemaitre Sécurité**

17 rue de Bitschhoffen - CS 90024  
F - 67350 Val de Moder  
Tél. +33 (0)3 88 72 28 80

**lemaitre-securite.com**



**LEMAITRE**

Safety since 1974

**DON\_LS 04 TDS 0092**  
updated: 21/07/21

Member of  
**SINAMAP**

