

# SAXO S3



Standard EN ISO 20345 : 2011

## LEMAITRE

*Safety since 1974*



### 200 J aluminum toe-cap

- light, wide and ergonomic
- imperceptible when worn

Size 38 to 47

Ref. SAXOS30NR

## Product Highlights



- **Water-repellent full-grain leather with nubuck finish:** a noble and very resistant material that helps fight against water infiltration.

- **Tongue with gusset** to prevent any infiltration of dust / pebbles.

- **Impact protection** on the outside of the shoe, malleolus protection

- **Padded collar** for everyday comfort

- **Comfort sole with shock absorbing heel pad:** impact and fatigue reduction, MSD prevention



- **Protection toe-cap:** aluminum



- **Puncture resistant midsole:** High tenacity fabric '0' penetration



## Anti-static sole STREET PU2D

- **Wider and flate sole offering great stability** for indoor and urban floors.

- **Shock absorption at the heel** for muscle fatigue prevention and comfort at a highlystrained zone.

- **Asymmetric profile 3 mm studs for reinforced grip**

- **Grooves for liquid dispersion for slip prevention.**

## USE

- Light industry, logistics, services, distribution, second-fixings



[lemaitre-securite.com](http://lemaitre-securite.com)

Lemaitre takes care.



# SAXO S3



Standard EN ISO 20345 : 2011

## Characteristics of the upper

- **Upper material:** water-repellent full grain leather with nubuck finish and reinforced toe cap
- **Tongue with gusset:** abrasion-resistant textile
- **Lining:** 3D microporous fabric

## Characteristics of the sole

- **Designation:** STREET
- **Material:** polyurethane / polyurethane
- **Antistatic sole**
- **SRA Adhesion coefficient:**  
forward flat slip: 0,42 (standard  $\geq 0,32$ )  
forward heel slip: 0,40 (standard  $\geq 0,28$ )
- **SRB Adhesion coefficient:**  
forward flat slip: 0,30 (standard  $\geq 0,18$ )  
forward heel slip: 0,16 (standard  $\geq 0,13$ )

## VARIANT



**Soul S3 SRC**  
SOULS30NR

## Practical information

Weight of one shoe size 42 : 550 g

AET N° LEC FI00374154

## Packaging

**shoebox** 360 x 220 x 135 mm

**carton** 680 x 460 x 370 mm

10 shoeboxes per carton

## Gencods

<b>38</b>	3237154013380	<b>43</b>	3237154013434
<b>39</b>	3237154013397	<b>44</b>	3237154013441
<b>40</b>	3237154013403	<b>45</b>	3237154013458
<b>41</b>	3237154013410	<b>46</b>	3237154013465
<b>42</b>	3237154013427	<b>47</b>	3237154013472

## Memo for basic and additional requirements of the standard EN ISO 20345: 2011

### Safety Footwear

<b>SBP</b>			
<b>S1</b>			<b>A</b> <b>E</b> <b>Fo</b>
<b>S1P</b>			<b>A</b> <b>E</b> <b>Fo</b>
<b>S2</b>			<b>A</b> <b>E</b> <b>Fo</b> <b>Wru</b>
<b>S3</b>			<b>A</b> <b>E</b> <b>Fo</b> <b>Wru</b>

200 J toe-cap: protection of the forefoot against impact and crushing.

Anti-perforation insert 1100 N: foot protection against perforation.

<b>A</b> Anti-static footwear	<b>Ci</b> Insulation against cold
<b>E</b> Shock absorption at the heel	<b>Hi</b> Insulation against heat
<b>Fo</b> Fuel oil-resistant outsole	<b>Hro</b> Outsole resistance to hot contact
<b>Wru</b> Water penetration and water absorption resistant upper	<b>Wr</b> Water resistant
Electrostatic discharge	<b>An</b> Ankle protection

**SRA** Slip-resistance on ceramic floors with detergent

**SRB** Slip-resistance on steel floors with glycerol

**SRC** = **SRA** + **SRB**

**Lemaitre Sécurité**  
17 rue de Bitschhoffen - CS 90024  
F - 67350 Val de Moder  
Tél. +33 (0)3 88 72 28 80

[lemaitre-securite.com](http://lemaitre-securite.com)

**LEMAITRE**  
Safety since 1974

Member of  
**SINAMAP**



**DON\_LS 04 TDS 0154**  
update: 22/06/23