

FREYR S3 Vibram®



Standard EN ISO 20345 : 2011



LEMAITRE

Safety since 1974



Ankle protection by Lemaitre

Malleolus protection against side impacts

Sizes 35 to 49

Ref. FREYS30NR

Product Highlights



▪ **Boot available with men's and women's fit.**



▪ **2,0 mm thick high strength leather** (against abrasion, tearing and puncture). Tongue with gusset to prevent any infiltration of dust / stones.

▪ **Scuffcap TPU injected:** extreme resistance at the front.

▪ **Memory Foam Titan insock for immediate and lasting comfort:** antibacterial properties, respects foot hygiene.



▪ **Protective toe-cap:** composite HDFC.



▪ **Puncture-resistant midsole:** high tenacity fabric "0" penetration.



TRAIL VIBRAM® sole
PU/antistatic nitrile rubber.



▪ **Exclusive technical sole** developed in partnership with Vibram®.

▪ **Semelle Outdoor** with excellent grip, Hi, HRO, adapted to difficult climatic conditions (hot and cold).

▪ **Excellent abrasion resistance.**

▪ **Raised heel (15 mm height)** for improved safety, especially on ladders.

USAGE

- Civil engineering and Forestry works
- Logistics, automotive
- Shipyard, construction
- Petrochemistry, oil platform



lemaitre-securite.com

An exacting attitude to quality is our culture, safety our priority



FREYR S3 Vibram®



Standard EN ISO 20345 : 2011

Characteristics of the upper

- **Upper material:** smooth full grain water-repellent leather with anti-abrasion TPU scuffcap
- **Tongue/gusset:** water-repellent leather
- **Collar:** water-repellent leather
- **Lining:** 3D microporous fabric

Characteristics of the sole

- **Designation:** TRAILIUM VIBRAM®
- **Material:** polyurethane / PU - caoutchouc nitrile - Vibram® antistatique
- **Antistatic sole**
- **SRA Adhesion coefficient:**
forward flat slip: 0,43 (standard $\geq 0,32$)
forward heel slip: 0,42 (standard $\geq 0,28$)
- **SRB Adhesion coefficient:**
forward flat slip: 0,23 (standard $\geq 0,18$)
forward heel slip: 0,19 (standard $\geq 0,13$)

VARIANT



Brimir S3 SRC
BRIMS30NR

Practical information

Women fitting 35-39

Weight of one shoe size 38:
790 g

CERTIFICATION N°
0075/007/161/12/20/2909
EXT 01/12/20

Men fitting 40-49

Weight of one shoe size 42:
870 g

CERTIFICATION N°
0075/007/161/12/20/2909

Packaging

size 35 to 49

shoobox 355 x 340 x 130 mm

carton 670 x 355 x 360 mm

5 shoeboxes per carton

Gencods

35	3237154402351	43	3237154402436
36	3237154402368	44	3237154402443
37	3237154402375	45	3237154402450
38	3237154402382	46	3237154402467
39	3237154402399	47	3237154402474
40	3237154402405	48	3237154402481
41	3237154402412	49	3237154402498
42	3237154402429		

Memo for basic and additional requirements of the standard EN ISO 20345: 2011

Safety Footwear

SBP



S1



S1P



S2



S3



200 J toe-cap: protection of the forefoot against impact and crushing.



Anti-perforation insert 1100 N: foot protection against perforation.



Anti-static footwear



Insulation against cold



Shock absorption at the heel



Insulation against heat



Fuel oil-resistant outsole



Outsole resistance to hot contact



Water penetration and water absorption resistant upper



Water resistant



Electrostatic discharge



Ankle protection



Slip-resistance on ceramic floors with detergent



Slip-resistance on steel floors with glycerol



SRC = SRA + SRB

Lemaitre Sécurité

17 rue de Bitschhoffen - CS 90024
F - 67350 Val de Moder
Tél. +33 (0)3 88 72 28 80

lemaitre-securite.com



LEMAITRE

Safety since 1974

DON_LS 04 TDS 0091
updated: 21/07/21

Member of
SINAMAP

