

# VITAMINE HAUTE S3 SRC



Standard EN ISO 20345 : 2011

## LEMAITRE

*Safety since 1974*



**ParaBolic®**  
Technology

- Excellent grip
- Anti-fatigue spring effect
- MSD prevention

Size 35 to 42

Ref. VIHNS30NR

### Product Highlights



- **Water-repellent suede leather 1.4-1.6 mm thick**, soft and resistant natural material.

- **Breathable model thanks to its 3D textile lining**: pleasant feeling of freshness. Ventilation of the foot inside the shoe.

- **Malleolus protection on the outside of the foot**

- **Anti-abrasion toe cap**, additional resistance of the resistance of the upper on the forefoot that ensures a long life of the product.



- **Label «Elected by women for women» awarded to the Vitamine Collection**



- **Toe cap**: steel



- **Puncture resistant midsole**: stainless steel



### Paraboline PU2D antistatic sole

- **Proportions specific to the morphology of the female foot**: comfortable footwear
- **Sole developed for industrial and urban floors**
- **Parabolic® patent** with dynamic anti-fatigue effect
- **Very good slip resistance**: +30% grip compared to the standard on SRA tiled ground.

### USE

- Construction, light industry, logistics, services, handling, distribution, transportation



[lemaitre-securite.com](http://lemaitre-securite.com)

Lemaitre takes care.



# VITAMINE HAUTE S3 SRC



Standard EN ISO 20345 : 2011

## Characteristics of the upper

- **Upper material:** Water-repellent split leather velvet finish and reinforced anti-abrasion toe cap
- **Lining:** 3D microporous fabric

## Characteristics of the sole

- **Designation:** Paraboline
- **Material:** PU / PU
- **Antistatic sole**
- **SRA Adhesion coefficient:**  
forward flat slip: 0,45 (standard  $\geq 0,32$ )  
forward heel slip: 0,42 (standard  $\geq 0,28$ )
- **SRB Adhesion coefficient:**  
forward flat slip: 0,22 (standard  $\geq 0,18$ )  
forward heel slip: 0,18 (standard  $\geq 0,13$ )

## VARIANT



**Vitamine basse S3**  
VIBNS30NR

## Practical information

Weight of one shoe size 37 : 440 g

AET N° F-230-02735-19

## Packaging

**shoebox** 317 x 199 x 104 mm

**carton** 565 x 415 x 325 mm

10 shoeboxes per carton

## Gencods

**35** 3237153795355

**36** 3237153795362

**37** 3237153795379

**38** 3237153795386

**39** 3237153795393

**40** 3237153795409

**41** 3237153795416

**42** 3237153795423

## Memo for basic and additional requirements of the standard EN ISO 20345: 2011

### Safety Footwear

SBP



S1



(A) (E) (Fo)

S1P



(A) (E) (Fo)

S2



(A) (E) (Fo) (Wru)

S3



(A) (E) (Fo) (Wru)

200 J toe-cap: protection of the forefoot against impact and crushing.

Anti-perforation insert 1100 N: foot protection against perforation.



Anti-static footwear



Insulation against cold



Shock absorption at the heel



Insulation against heat



Fuel oil-resistant outsole



Outsole resistance to hot contact



Water penetration and water absorption resistant upper



Water resistant



Electrostatic discharge



Ankle protection



Slip-resistance on ceramic floors with detergent



Slip-resistance on steel floors with glycerol



= SRA + SRB

**Lemaitre Sécurité**  
17 rue de Bitschhoffen - CS 90024  
F - 67350 Val de Moder  
Tél. +33 (0)3 88 72 28 80

[lemaitre-securite.com](http://lemaitre-securite.com)

**LEMAITRE**  
Safety since 1974

Member of  
**SINAMAP**



**DON\_LS 04 TDS 0155**  
update: 22/06/23