

FilterSpec® Pro

FilterSpec® Pro zwart/helder FFP2V / AGE120-201-100



BESCHRIJVING

Veiligheidsbrillen en ademhalingsstoestellen die samen worden gedragen, verminderen vaak elkaars doeltreffendheid omdat brilmonturen de afdichting van het ademhalingsstoestel in gevaar brengen en leiden tot lensverneveling en verminderde ademhalingsbescherming. FilterSpec®Pro combineert beide beveiligingen in een geïntegreerde eenheid.

OPTIES

FilterSpec® Pro zwart/helder FFP2V (AGE120-201-100)

FilterSpec® Pro zwart/helder FFP3V (AGE130-201-100)

VEILIGHEIDSNORMEN

EN 170 • EN 149 • EN 166



SPECIFICATIES



RADIATION PROTECTION BREAKDOWN filtering effect
Scale Number
2C



LIGHT TRANSMISSION BREAKDOWN Lens Shade number
1,2



Manufacturer's Trademark
JSP Dolk



Optical Class (1 – Class 1 – High quality for regular use. 2 – Class 2 – Medium quality for occasional use. 3 – Class 3 – Low quality for exceptional use)
1



Medium Energy Impact resists a 6 mm, 0.86g ball @ 120 m/s Maximum protection for goggles.
B



The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures. (-5°C and +55°C) Optional
T



Protection from Liquid Droplets
3



Resistance to Molten Metals and Hot Solids Helmets (optional)
9



Protection from Large Dust Particles (up to 40 um grain size)
4



Filter Type
P (Beschermt tegen vaste en vloeibare aerosolen)

Classification
FFP2 (deeltjesfilterend gelaatsstuk)



Activated Carbon Layer
Nein

Usage
NR (Niet-herbruikbaar)

Maximum Total Inward Leakage (TIL)
8%

Minimum Filtration Efficiency
94% voor FFP2 Gewaardeerd

UK Assigned Protection Factor
10

Nominal Protection Factor
12



Exhalation Valve
Ja

Mask Design
Gevormd

Material
Polycarbonaat lens

Mask Material
Polypropyleen



Product Weight
144g

Material
HDPE maskerhouder

KENMERKEN




Integratie

Het unieke ontwerp van FilterSpec maakt een einde aan het probleem van slecht passende maskers, beslagen lenzen en non-conformiteit dat vaak optreedt wanneer het ene PBM-onderdeel het andere compromitteert.



Kwaliteitsglas

De FilterSpec® Pro goggle heeft een 5.5 base curve lens. FilterSpec® lenzen hebben een basiscurve van 6,5. Beide bieden optimale dekking en zijn voorzien van anticondens en antikras lenscoatings.



Efficiënt filter

De eenvoudig te vervangen filters bestaan uit drie lagen voor uitzonderlijke prestaties. Verkrijgbaar met uitademventiel met lage weerstand om ophoping van vocht en CO2 te verminderen.

BEREIK

DOWNLOADS



[Pakket afbeeldingen \(ZIP\)](#)



[doc-filterspec-pro-ffp2-mask.pdf \(PDF\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 3 / Issued 23 Feb 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.





JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 3 of 3 / Issued 23 Feb 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.

