

## EVOGuard®C5-MAX Industrieel vizier

EVOGuard®C5-MAX / ADA280-070-000



### BESCHRIJVING

EVOGuard®C hoogwaardige industriële vizieren bieden uitgebreide gezichtsbedekking zonder de bewegingsvrijheid te beperken. Het vizier van optische klasse 1 biedt UV-bescherming en een panoramisch zicht met minimale vervorming.

Het C5-MAX vizier, dat compatibel is met \*EVO® helmmodellen, biedt een slagvastheid tot AT en is voorzien van een geïntegreerde kinbeschermer voor extra bescherming. De EVOGuard® C5 Max moet worden gebruikt als onderdeel van een arc flash beschermend ensemble dat ook geschikte arc flash beschermende kleding en handschoenen bevat.

\*Exclusief EVO®6100 assortiment.

### OPTIES

#### **EVOGuard®C5-MAX (ADA280-070-000)**

EVOGuard® C5-MAX industriële vizierkit K&N - EVO® VISTA® compatibel (ADA280-070-00C)

### VEILIGHEIDSNORMEN

EN 166 • EN 170 • GS-ET-29



## SPECIFICATIES



**RADIATION PROTECTION BREAKDOWN** filtering effect  
Scale Number  
2C



**LIGHT TRANSMISSION BREAKDOWN** Lens Shade number  
1,2



Manufacturer's Trademark  
JSP Dolk



High Energy Impact resists a 6 mm, 0.86g ball @ 190 m/s  
Maximum protection for face shields  
**A - Alleen voor montage op EVO® helmen**



Protection from Liquid Splash  
3

Arc Flash Protection Class  
1: Tot 4kA, of 155kJ/m<sup>2</sup> of 3,7cal/cm<sup>2</sup>



Resistance to Molten Metals and Hot Solids Helmets  
(optional)  
9



Resistance to fogging (optional)



BSI Kitemark  
Ja



Product Weight  
216g



Kit  
Geleverd met: EVO®2,3,5,DS, Lite, Skyworker™  
armen. EVO8/EVOLite Badgehouder Armen.



Optical Class (1 – Class 1 – High quality for regular use. 2 – Class 2 – Medium quality for occasional use. 3 – Class 3 – Low quality for exceptional use)  
1



The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures. (-5°C and +55°C) Optional  
T



Protection Against Short Circuit Electric Arc  
8



Visible Light Transmittance (VLT)  
0: ≥ 75%



Resistance to Surface Damage by Fine Particles (optional)  
K



Visor Length  
21,5 cm

Material  
Polycarbonaat Schild



Recyclable  
Ja

UI  
[https://www.jspgo.com/UI-HD/UI\\_EVOGuard/UI-Pages/InstructionImages.png](https://www.jspgo.com/UI-HD/UI_EVOGuard/UI-Pages/InstructionImages.png)

## KENMERKEN



### Compatibiliteit

EVOGuard® vizieren maximaliseren de compatibiliteit met JSP halfgelaatsmaskers, wegwerpbare ademhalingsmaskers, brillen op sterkte en de Sonis® op de helm gemonteerde oorbeschermers.



### Impact

Breed assortiment hoogwaardige vizieren die tot A-klasse schokbestendigheid bieden wanneer ze op een veiligheidshelm zijn gemonteerd en bescherming tegen gemiddelde energie-impact met de EVOGuard® wenkbrauwbeschermer.



### Elektrische vlamboogbeveiliging

EVOGuard® C5 MAX voldoet aan de vereisten van GS-ET-29 en biedt oog- en gezichtsbescherming tegen het risico van een vlamboog: GS-ET-29 klasse 1, 4kA (155kJ/m<sup>2</sup>) en 3,7 Cal/cm<sup>2</sup>.



### Visie

Het vizier van optische klasse 1 biedt een panoramisch zicht met minimale vervorming, ideaal om de hele dag comfortabel te dragen.



### Dekking

EVOGuard®-vizieren bieden uitgebreide gezichtsbedekking zonder de bewegingsvrijheid te beperken. EVOGuard® MAX-vizieren bieden een verbeterde bedekking met een geïntegreerde kinbeschermer.



### UV-bescherming

Het vizier filtert schadelijke UV-straling om de ogen te beschermen en biedt tegelijkertijd een hoge lichttransmissie en verbeterde kleurherkenning.



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: [sales@jspgo.com](mailto:sales@jspgo.com) / Web: [www.jspgo.com](http://www.jspgo.com)

Do Not Publish without written permission from JSP Limited. Contact [copyright@jspgo.com](mailto:copyright@jspgo.com). Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 3 / Issued 23 Feb 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.





 [www.youtube.com/watch?v=\\_VnTgBRRT9E](https://www.youtube.com/watch?v=_VnTgBRRT9E)

## DOWNLOADS

 [Pakket afbeeldingen \(ZIP\)](#)

 [doc-evoguard.pdf \(PDF\)](#)



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: [sales@jspsafety.com](mailto:sales@jspsafety.com) / Web: [www.jspsafety.com](http://www.jspsafety.com)

Do Not Publish without written permission from JSP Limited. Contact [copyright@jspsafety.com](mailto:copyright@jspsafety.com). Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 3 of 3 / Issued 23 Feb 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.

